



GENERAL DATA

Luminaire type	Housing and utilities
Installation	horizontal or vertical surface
Environment	Indoor and outdoor
Body material	Die casting aluminum Stainless steel screws
Diffuser	Milky white PC
Finish color	Black / white / grey
Standard	CE
IP rating	IP 65
Operating	-30° ~ +40° C
Dimensions (LxWxH)	275 x 275 x 80 mm
Net weight	1,5 kg
Warranty	5 years
PF	≥ 0,90
IK	10



ELECTRICAL DATA

Power	15 W 20 W
Input volt	220 - 240V
Frequency	50 ± 10% Hz
Connections	Live, Earth, Neutral
Class	I, must be earthed
Lifespan	50 000 hrs

LIGHTING DATA

Luminous flux	1 350 lm 1 800 lm
LED color	3 000 4 000 6 000 K
Color rendering index	> 80 Ra



APPLICATIONS

- housing infrastructure
- utility rooms
- adjacent territories
- corridors and passages

FEATURES

- Flicker-free LED Driver (optional)
- Daylight sensor (optional)
- Microwave sensor (optional)
- DALI control (optional)
- ZigBee control (optional)
- Emergency (optional)

*The luminaire complies with fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.

The information is for your reference only, we reserve the right to make alterations in the interest of improving our products.